

PRODUCT OFFERING LINE SHEET



Load Bearing Roller Assemblies

Cam Followers

Diameters: 2" through 20" – Full Complement Needle Bearings

DCB Rollers

Diameters: 2" through 10" – Full Complement Cylindrical Roller Bearings

XR Rollers

Diameters: 1" through 10" – Ball Bearings or Tapered Roller Bearings

Track Rollers

Diameters: 1" through 20" – Ball Bearings or Tapered Roller Bearings

Custom & Made-To-Order

Custom solutions made viable through extensive product knowledge, application assistance and *catalog-like* availability



Conveyor Pulleys

FC & MC Series Drum Pulleys

Diameters: 2" through 12.75" - Featuring PCI Trapezoidal Crown Technology

Heavy Duty & Mine Duty Drum Pulleys

Diameters: standards up to 60" - Featuring PCI Contoured Integral End Disks

Self-Cleaning Wing Pulleys

Diameters: 2" through 52" - Featuring The Eradicator®-The World's First True Wing Hybrid

Stainless Steel Conveyor Pulleys

Diameters: 2" through 60" - Featuring Refined Classes for Painless Stainless Selection



Accessories

Take-Up Frames & Covers

Narrow & Wide Slot, Center Pull, Top Angle, Light & Heavy Duty Protected Screw, and Telescoping Style

Lagging & Coating Services

Cold bonded, weld-on replaceable and over twenty hot vulcanized compounds

Stainless Steel Compression Hubs & Bushings

Several styles manufactured from 300 grade stainless steel materials

Axles & Shafting

Multiple diameters and materials with extensive capacity in custom detailing



Pneumatic Clutches & Brakes

PCI Pneumatic Clutches, Brakes and Clutch/Brakes are IDEALLY suited for

- Accumulation, Zone or Zero-Pressure conveyor systems
- Occasional starts and stops, no more than 5 cycles per minute
- High torque capacities from 0 to 6,300 inch pounds
- Low speed – less than 100 RPM

